

## The FEM-prediction on Tensile Performance of Woven Membrane Materials Under Uni and Bi-axial Loads

Shou-Hui Chen<sup>1,2\*</sup>, Hong-Qin Yu<sup>1,2</sup>, Zheng Guo<sup>1,2</sup>, Raul Figueiro<sup>3</sup>, Da-Peng Qi<sup>1</sup>

<sup>1</sup>College of Textile, Zhongyuan University of Technology, Zhengzhou, Henan, 450007, China

<sup>2</sup>Henan Key Laboratory of Functional Textiles Material, Zhengzhou, Henan, 450007, China

<sup>3</sup>Department of Textile Engineering, School of Engineering, University of Minho, Campus of Azurem, Guimaraes, 4800-058, Portugal

**Abstract:** In this study, the mechanical model of the woven PVC-coated membrane materials has been built. By the FEM analysis, it was found out that when tensioned under uni-axial loads, the tensile modulus in the warp and fill direction of woven membrane materials could be predicted nicely, especially after the revision of the properties for the fiber materials. The effect of the tensile moduli of the fiber and the PVC coating materials on the modulus of the woven membrane fabrics has been discussed. It could be consulted that with the proper improvement of the modulus of the fiber materials in the fill direction, the discrepancy between the modulus of woven membrane materials in the warp and fill direction could be reduced to a certain extent. When it comes to the prediction of the modulus of the woven membrane materials under bi-axial loads, large difference could be noticed between the predicted results and the experimental results, especially in warp direction. This was due to the fact that the mechanical analysis model could only show the differences of the geometry configuration between the warp and fill directions. However, the reinforcement of membrane materials in warp direction during weaving and coating processes has been ignored.

**Keywords:** FEM, membrane materials, coated fabrics, tensile modulus, uni-axial, bi-axial

### References:

- developments. *The Structural Engineer* 2004; 82: 21-27.
- [1] Minami H. Deflection and tension properties of coated fabrics subjected to lateral pressure. In: Proc Proc of Conf Engineering Software. University of Southampton, September 1979; 123-144.
- [2] Chen Y, Lloyd DW, Harlock SC. Mechanical characteristics of coated fabrics. *J Textil Inst* 1995; 86: 690-700.
- [3] Hino Y, Ishii K. An evaluation method on the material nonlinearity in the analysis of membrane structures. In: Proc Membrane structures association of Japan 1994; 35-49.
- [4] Minami H, Yamamoto C, Segawa S, Kono Y. A method for membrane material nonlinear stress analysis using a multi-step linear approximation. In: Proc IASS Int Symp on Shell and Spatial Structures. Singapore 1997; 595-602.
- [5] Bridgens BN, Gosling PD, Birchall MJS. Tensile fabric structures: concepts, practice &
- [6] Bridgens BN, Gosling PD, Birchall MJS. Membrane material behavior: concepts, practice & developments. *The Structural Engineer* 2004; 82: 28-33.
- [7] Menges G, Meffert B. Mechanical behaviour of PVC-coated polyester fabrics under biaxial stress. *Kunststoffe* 1976; 66: 741-745.
- [8] Stubbs N, Fluss H. A space-truss model for plain-weave coated fabrics. *Appl Math Model* 1980; 4: 51-58.
- [9] Schock HJ. On The Structural behavior and material characteristics of PTFE-coated glass-fiber fabric. *J Ind Textil* 1991; 20: 277-288.
- [10] Kato S, Yoshino T, Minami H. Formulation of constitutive equations for fabric membranes based on the concept of fabric lattice model. *Eng Struct* 1999; 21: 691-708.

- [11] Pargana JB. Realistic modeling of tension fabric structures. Doctor. London. Imperial College 2004.
- [12] Chen SH, Ding X, Yi HL. On the anisotropic tensile behaviors of flexible polyvinyl chloride-coated fabrics. *Textil Res J* 2007; 77: 369-374.
- [13] Chen SH, Ding X, Fanguero R, Yi HL, Ni J. Tensile behavior of PVC-coated woven membrane materials under uni-and bi-axial loads. *J Appl Polymer Sci* 2008; 107: 2038-2044.
- [14] Luo GJ, Ding X, Chen SH, Hu C. Effects of fabric extension during coating on the tensile performance of membrane material. *J Textil Res* 2007; 28: 47-51. (in chinese).